

Mag Pro 3



- Three - component anti - chip compound, highly resistant to impacts.
- Provides high protection of power body and under body sections.
- OE factory quality without sanding.
- Can be painted after 30 min.
- Apply with a primer gun.

Description	Packaging	Part No.
Mag Pro 3	1.5 Kg	77 11 218 364

Voc content: 613.7 grammes / pack

MJ Pro black / white PU

- Single component sealer.
- Excellent adhesion.
- Overpaintable after 20 min at 23°C.
- Remains highly flexible.
- Can be spot welded through.
- Apply with either Betapress or standard Caulking gun.



Description	Packaging	Part No.
MJ Pro white	310 ml cartridge	77 11 172 677
MJ Pro black	310 ml cartridge	77 11 172 676
Betapress gun +	1 unit	77 11 171 310
Nozzle	1 unit	77 11 171 908
Caulking gun +	1 unit	77 01 423 763
Nozzle	1 unit	77 11 171 908

Voc content: 20.63 grammes / pack

Voc content: 20.29 grammes / pack

MEG - preformed door panel sealant



- Seals and bonds plastic membranes to door structures.
- Quick and simple ready to use product.
- OE factory fit.
- No special tools required.

Description	Packaging	Part No.
Sealant mastic	1 unit	77 01 423 330

Supplied in box of 20 rolls.

thumbing compound

- High adhesion when applied using finger pressure only.
- Immediately overpaintable.



Description	Packaging	Part No.
Thumbing compound	60 rolls ø 6 and 300 mm	77 11 170 230

brushable seam sealer



- Waterproof.
- Oil resistant.
- Does not sag.
- Overpaintable.
- Drying time: 2h at 20°C.

Description	Packaging	Part No.
Brushable seam sealer	pot of 1 kg	77 11 228 113

Voc content: 450.0 grammes / pack

adhesives & glues

neoprene aerosol adhesive

- Quick drying.
- Easy to apply.
- Excellent resistance up to 95°C.



Description	Packaging	Part No.
Neoprene aerosol	500 ml	77 11 170 227

Voc content: 443.0 grammes / pack